

ATC High Temperature Radiant Ceiling Heaters

Key Features Include:

- Energy efficient
- Draught and noise free
- Can be ceiling or wall mounted with optional tilt wall brackets
- Optional protective grille available
- Attractive finish
- Three panel heat outputs available: 1800W, 2400W, 3600W



Providing an economical and draught free means of heating in commercial, agricultural and industrial premises.

Technical Details

Model	ATC Ecosun High Temperature Radiant Panels		
Product Code	S18-PLUS	S24-PLUS	S36-PLUS
Colour	White / Grey	White / Grey	White / Grey

Electrical Specifications

Voltage (Volts)	230-240 Vac 1Ø	230-240 Vac 1Ø	380-415 Vac 3Ø
Frequency (Hertz)	50	50	50
Power (Watts)	1800	2400	3600
Running Current (Amps)	7.8	10.4	5 (per Ø)
Insulation Class	CL.I	CL.I	CL.I

Mounting & Installation

Installation	Ceiling / Wall*	Ceiling / Wall*	Ceiling / Wall*
Dimensions (HxWxD) mm	60 x 250 x 1500	60 x 250 x 1500	60 x 350 x 1500
Weight (Kg)	9.9	9.9	13.9
IP Rating	X4	X4	X4

* Wall mounted with optional separate bracket

Ecosun Accessories

Code	Ecosun Accessories
5401785 -PLUS	Tiltable Wall Brackets for S18, S24 & S36 Heaters
5401792	Protective Grille for S18 & S24 Ecosun Heater
5401794	Protective Grille for S36 for Ecosun Heater

Design Facility

We are committed to providing comprehensive technical support for all your radiant ceiling heating projects. We now offer the most comprehensive design service yet. Simple sketches and dimensions can be converted into a professional drawing plan and quotation. All plans can be electronically sent and received for maximum efficiency e-mail: sales@atcelec.co.uk